# CX540D



Coaxial Relay SPDT 3x BNC, 12VDC

Rating: Not Rated Yet
**Price:**
Sales price without tax: 115,88 €

Ask a question about this product

Description

| | |
|---|---|
| **MECHANICAL / TERMINAL PROPERTIES** | |
| Contact Material | Gold |
| Mechanical life (cycles) | 10 x 10^6 |
| Electrical life (cycles) | 10 x 10^4 |
| Weight | Approx. 200 g |
| Terminals | Screw terminals |
| Mounting Position | Any position recommended |
| **ELECTRICAL / TERMINAL PROPERTIES** | |
| Contact Rating | 30 W/VDC |
| Operating Voltage | 12 VDC |
| Voltage drop | Max. 0.1 V / 1 A |
| Insulation Resistance | Min. 1000 MΩ / 500 VDC |
| Dielectric Strength | 2k volts 50/60 Hz 1 min |
| **CONDITIONS** | |

| Frequency | Loss | Frequency | Loss | Frequency | Loss |
|---|---|---|---|---|---|
| MHz | (dB) | MHz | (dB) | MHz | (dB) |
| 0 | 0.00 | 1000 | 0.17 | 2000 | 0.25 |
| 100 | 0.05 | 1100 | 0.18 | 2100 | 0.26 |
| 200 | 0.07 | 1200 | 0.19 | 2200 | 0.27 |
| 300 | 0.09 | 1300 | 0.20 | 2300 | 0.28 |
| 400 | 0.11 | 1400 | 0.21 | 2400 | 0.29 |
| 500 | 0.12 | 1500 | 0.22 | 2500 | 0.30 |
| 600 | 0.13 | 1600 | 0.23 | 2600 | 0.31 |
| 700 | 0.14 | 1700 | 0.24 | 2700 | 0.32 |
| 800 | 0.15 | 1800 | 0.25 | 2800 | 0.33 |
| 900 | 0.16 | 1900 | 0.25 | 2900 | 0.34 |