

CX-600NC



Relay for use up to 1,5 GHz. For 1 kW PEP. Low insertion loss.

Rating: Not Rated Yet

Price:

Sales price without tax: 100,76 €

[Ask a question about this product](#)

| Description | Technical Data | CX 600 NC |
|-------------|-----------------------|---|
| | Pull-in voltage | 10-14 V |
| | Pull-off voltage | 3 V DC |
| | Operating voltage | 12 V DC at 160 mA/20° C |
| | Pull-in time | 20 ms typ. |
| | Pull-off time | 15 ms typ. |
| | Contact type | 1x UM |
| | Operating temperature | -50° C - +70° C |
| | Weight | ca. 230 g |
| | Installation | 2 screws, 1 N-socket, 2x cable connection |

| HF characteristics Frequency | VSWR | Isolation | Insertion loss | max. HF power |
|---------------------------------|------|-----------|----------------|---------------|
| 50 MHz | 1,03 | 60 dB | 0,07 dB | 1000 W |
| 150 MHz | 1,1 | 48 dB | 0,1 dB | 1000 W |
| 500 MHz | 1,15 | 37 dB | 0,15 dB | 800 W |
| 1000 MHz | 1,2 | 28 dB | 0,2 dB | 500 W |
| 1500 MHz | 1,2 | 26 dB | 0,2 dB | 350 W |
| 2000 MHz | 1,25 | 23 dB | 0,23 dB | 100 W |