

CX-140D



Coaxial Relay SPDT 1x N, 2x cable, 12VDC

Cena

Predajná cena bez DPH: 67,14 €

[Opýtajte sa na tento produkt](#)

| Popis produktu | Technical Data | CX 140 D |
|----------------|-----------------------|-----------------------------------|
| | Pull-in voltage | 10-14 V |
| | Pull-off voltage | 3 V DC |
| | Operating voltage | 12 V DC at 80 mA/20° C |
| | Pull-in time | 15 ms typ. |
| | Pull-off time | 10 ms typ. |
| | Contact type | SPDT |
| | Operating temperature | -25° C - +50° C |
| | Weight | ca. 95 g |
| | Installation | N-Female, directly connect cables |

| HF characteristics Frequency | VSWR | Isolation | Insertion loss | max. HF power |
|---------------------------------|------|-----------|----------------|---------------|
| 50 MHz | 1,03 | 55 dB | 0,08 dB | 250 W |
| 150 MHz | 1,03 | 51 dB | 0,10 dB | 250 W |
| 500 MHz | 1,05 | 47 dB | 0,15 dB | 200 W |
| 1000 MHz | 1,60 | 34 dB | 0,20 dB | 150 W |
| 1500 MHz | 1,02 | 28 dB | 0,25 dB | 100 W |

